



INSUL-ANCHORS

GUIDELINES FOR SELF-STICK INSUL-ANCHORS

1. MUST BE APPLIED TO A **CLEAN, NONPOROUS** SURFACE, THAT IS FREE OF ALL OIL, FILM, DUST, RUST, ETC.
2. NOT GENERALLY RECOMMENDED ON **PAINTED SURFACES** NOR CEILINGS OF METAL BUILDINGS.
3. BEST RESULTS ARE OBTAINED WHEN AMBIENT TEMPERATURE IS ABOVE 40°F (5°C). AT TIME OF APPLICATION.
4. TEMPERATURE RANGE FOR THE FOAM TAPE IS FROM -20° to +150°F (-30° to +65c°C).
5. LOADING SHOULD NOT EXCEED 3 LBS. PER ANCHOR. (.75 lbs/sq. inch)
6. BASE MUST BE APPLIED WITH **FIRM** PRESSURE. DO NOT TWIST DURING APPLICATION. DO NOT REMOVE RELEASE (BACKING) PAPER UNTIL READY TO USE.
7. INSULATION MAY BE APPLIED IMMEDIATELY AFTER BOND IS MADE
8. NOT RECOMMENDED FOR USE ON SINGLE SKIN ROOFDECKS

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied.

Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product.

Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer

**All information contained herein is subject to change without notice.
For more information-consult your nearby Continental Field sales representative.**

