



Spec. Sheet No. GPA-72

MSDS

[Click for Material Safety Data Sheet](#)

tactoo® ADHESIVE

| | | |
|---|---|--|
| DESCRIPTION | <p>TACTOO® GPA-72 ADHESIVE IS ESPECIALLY FORMULATED TO BOND AGM INSUL-HANGERS OR SIMILAR CLIPS, TO METAL, MASONRY AND OTHER SOUND SUBSTRATES. SURFACES MUST BE CLEAN AND DRY BEFORE ADHESIVE IS APPLIED. POORLY BONDED OR SCALY PAINT FILMS SHOULD BE SCRAPPED TO ALLOW ADHESION TO BASE MATERIALS. SOME PROTECTIVE, COATINGS ARE NOT COMPATIBLE WITH GPA-72. MAKE TEST BONDS BEFORE PROCEEDING.</p> | |
| APPLICATION | <p>APPLY A BLOB OF GPA-72 THE SIZE OF A SMALL WALNUT TO BASE OF THE HANGER WITH A PUTTY KNIFE AND QUICKLY PRESS THE HANGER INTO PLACE USING A TWISTING MOTION. ADHESIVE SHOULD BE 1/32" TO 1/16" THICK OVER THE ENTIRE HANGER BASE AFTER IT HAS BEEN FIRMLY PRESSED INTO PLACE. PREPARE AND ATTACH ONLY ONE (1) HANGER AT A TIME. THIS METHOD MUST BE FOLLOWED TO INSURE COMPLETE ADHESION.</p> | |
| PROPERTIES | <p>BASE. COLOR. TEMP. RANGE. SOLIDS. WEIGHT. SOLVENT. STORAGE TEMP. DRYING TIME BONDING TIME CONSISTENCY. FLASH POINT.</p> | <p>NEOPRENE RUBBER GRAY/TAN -30° F. TO + 225 °F. APPROX 48% BY WEIGHT APPROX 8.8 LBS PER GAL. TOLUOL 60° F. TO 80° F. UP TO 48 HRS. UP TO 10 MINS. HEAVY MASTIC + 50° F.</p> |
| CAUTIONS | <p>DO NOT THIN GPA-72. EXTREMELY FLAMMABLE. KEEP AWAY FROM SPARKS OR FLAME AND BE SURE TO PROVIDE ADEQUATE CROSS VENTILATION DURING APPLICATION.</p> | |
| PACKAGING | QUARTS. | 12 PER CARTON |
| | GALLONS | 4 PER CARTON |
| <p>ALL STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON TESTS WE BELIEVE TO BE RELIABLE, BUT THE ACCURACY THEREOF IS NOT GUARANTEED, IT BEING SPECIFICALLY UNDERSTOOD THAT THERE ARE NO WARRANTIES EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS, SUITABILITY OF USE OR OTHERWISE INCIDENT TO THE SALE OF THIS PRODUCT. NO PERSON IS AUTHORIZED OR EMPOWERED TO MAKE ANY STATEMENT OR RECOMMENDATION CONCERNING SAID PRODUCT NOT CONTAINED HEREIN, AND ANY SUCH STATEMENT OR RECOMMENDATION SO MADE SHALL NOT BIND THE COMPANY. USERS ASSUME ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF THIS PRODUCT AND MUST CONFIRM THE ADAPTABILITY THEREOF BY THEIR OWN TESTS.</p> | | |
| <p>THIS PRODUCT IS MIRACLE ADHESIVE NO. MA-4062 (FORMERLY HT-4620)</p> | | |

**All information contained herein is subject to change without notice.
For more information-consult your nearby Continental Field sales representative.**